

## MINE MARK Blast & Survey Marker

Non-flammable blast & survey marker

A single component, quick drying mine / blast & survey marking spray with a specially designed actuator that allows for upright, inverted, or horizontal spray.

### Intended Uses:

MINE MARK Blast & Survey Marker is a non-flammable marking paint designed for spray application for above ground and underground applications. Used for creating temporary, highly visible markings on rock faces and rough, uneven surfaces which may be wet, dry, or dusty.

Suitable for use in mine & blast marking applications as well as construction, landscaping, civil works & surveying.


### Properties:

- High opacity, high quality, and high pigment loading.
- Easy to use aerosol.
- Provides a lasting high visibility mark.
- Adheres well to damp rock.
- Will not wash away when dry.
- Fast drying.
- Non-flammable (flame extension test method).
- Does not contain CFC's ozone depleting substances, lead, or chromates.

### Technical Data:

Solid Colours	White, yellow, Blue, Red, Black, Green & Orange
Signal Colours	Yellow, Orange, Red, Violet, Blue, Green, Grey & Brown
Fluorescent / Luminescent Colours	Red, Blue, Green, Yellow, Orange & Pink
Finish	Matt
Valve	360°
Actuator/Nozzle	Jet spray
Method of Application	Aerosol spray
Theoretical Coverage	2 – 4 m <sup>2</sup> per can depending on coverage
Pack size	400gm
Tariff/ HS Code	32082090

### Application:

Mixing	<p>Ensure that the can is shaken well as per the below instructions.</p> <p>Shake the can vigorously for 2 minutes or until the ball is rattling.</p>
Aerosol	<p>Point and spray at the areas requiring marking. After use invert can and spray to clean out the nozzle.</p> <div style="display: flex; justify-content: space-around; align-items: center;">   </div>

## Drying Information:

	0°C	5°C	15°C	25°C	40°C	45°C
Touch Dry	-	-	-	5 min	-	-
Hard Dry	-	-	-	30 min	-	-

## Disposal:

Aerosol should be completely emptied prior to disposal.

Contents of can are under pressure and should not be punctured or incinerated even when empty.

When empty, dispose of container through an approved recycling scheme or seek advice from your local council regarding accepted disposal methods.

## Limitations:

- Make sure to read the safety instructions. (SDS)
- Technical and application data herein is for the purpose of establishing a general guideline of the coating application procedures.
- Test performance results were obtained in a controlled laboratory environment and UG Mining makes no claim that the exhibited published test results, or any other tests, accurately represent results found in all field environments. As application, environmental and design factors can vary, due care should be exercised in the selection and verification of the performance and use of the coating.

## Pack Size:

Aerosol – 400gm (12 per carton)

## Storage:

- Shelf Life: 24 months at 25°C from date of manufacture. Subject to inspection thereafter.
- Store can with nozzle on, and in dry conditions out of direct sunlight away from sources of heat or ignition.
- Store at temperatures between 5°C and 35°C.

## Precautions:

For complete safety and handling information please refer to the appropriate Safety Data Sheets prior to using this product.

Whilst we endeavour to ensure that all advice we give about the product is correct, the information given in this data sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so entirely at his own risk. As conditions of use, method of application and suitability of the substrate prior to painting are beyond our control, no guarantee is implied by the recommendations contained herein. We therefore do not accept any liability whatsoever or howsoever arising from the performance of this product or for any loss or damage arising out of the use of this product. The information contained in this sheet is liable to modification from time to time in the light of experience and ongoing product development programmes. It is the user's responsibility to ensure that this sheet is current prior to using the product